




BALTI 150 1800LM
Design: Enrico Davide Bona and Elisa Nobile


Product code	Color
118503	Silver
118504	White

General Specifications

Product type	: Wall-bracket
Mounting type	: Wall - surface
Description	: Balti 150 is a single-light exterior wall-mounted luminaire, designed to be equipped with COB LED of last generation, with passive heat dissipation. The light beam of Balti has been specially designed to ensure a wide lighting of the wall, of the ceiling and of the floor, with an excellent glare control. IP66.
Indoor/outdoor lights	: Outdoor
Applications	: Corridors, Gardens, Halls, Open galleries, Passage areas, Terraces

Lighting specifications

Lamp description	: LED 1800lm 12W 3000K CRI85
Nominal lumens on thermal regime	: 1800
Efficiency L.O.R. (%)	: 75
Delivered lumens (lm)	: 1348
Lamp wattage (W)	: 12
Color temperature (K)	: 3000
Average lamp life (h)	: L80B10 50.000
Photobiological risk group	: RG1

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted, with a special antioxidising pretreatment
Closing Screen	: Tempered glass
Thermal Dissipation	: Passive

Electrical Specifications


Glow wire (°C)	: 850
Driver	: Included
Driver mounting	: Integrated
Voltage (V)	: 220/240
Frequency (Hz)	: 50/60

Weight and Dimensions












Length (mm)	: 48
Width (mm)	: 163
Height (mm)	: 158
Weight (Kg)	: 1,1

Optical Specifications

Aiming	: Fixed
Light distribution	: Asymmetric
Light beam	: 110°

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	12	1800	3000	85

Photometrics

1185 Gamma Angles 180° 120° 90° 75° 60° 45° 30° 15° 0° 15° 30° 100° 200° 300° 400° 500° cd/klm	BALTI 150 LED 12W 1800 lm				R:100%		I.Max:457 Cd/Klm			
	H[m]	D[m]	Max lux	Med lux	Alpha=111°	H[m]	D[m]	Max lux	Med lux	Beta=93°
	1.00	2.96	535	127		1.00	2.84	535	127	
	2.00	5.92	134	32		2.00	5.68	134	32	
	3.00	8.88	59	14		3.00	8.52	59	14	
	4.00	11.84	33	8		4.00	11.36	33	8	
	5.00	14.80	21	5		5.00	14.20	21	5	

Pictures and Applications

