

Product code	Color
119803	Silver
119804	White

General Specifications

Product type	: Wall-bracket
Mounting type	: Wall - surface
Description	: Balti 220 is a bidirectional exterior wall-mounted luminaire, designed to be equipped with COB LED of last generation, with passive heat dissipation. The light beam of Balti has been specially designed to ensure a wide lighting of the wall, of the ceiling and of the floor, with an excellent glare control. IP66.
Indoor/outdoor lights	: Outdoor
Applications	: Arcades, Corridors, Gardens, Halls, Terraces, Walkways

Lighting specifications

Lamp description	: LED 2x3400lm 2x26W 3000K CRI85
Nominal lumens on thermal regime	: 3400
Efficiency L.O.R. (%)	: 82,3
Delivered lumens (lm)	: 2798
Lamp wattage (W)	: 26
Color temperature (K)	: 3000
Average lamp life (h)	: L80B10 50.000
Photobiological risk group	: RG1

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted, with a special antioxidising pretreatment
Closing Screen	: Tempered glass
Thermal Dissipation	: Passive

Electrical Specifications

Glow wire (°C)	: 850
Driver	: Included
Driver mounting	: Integrated
Cable gland	: Nickel-plated brass
Voltage (V)	: 220/240
Frequency (Hz)	: 50/60

Weight and Dimensions


Length (mm)	: 166
Width (mm)	: 56
Height (mm)	: 225
Weight (Kg)	: 1.9

Optical Specifications

Light distribution	: Asymmetric
Light emission	: Bi-directional
Light beam	: 100/100

BALTI 220 BI-DIRECTIONAL 2X3400LM

Design: Enrico Davide Bona and Elisa Nobile

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	26	3400	3000	85

Pictures and Applications

